

(19)

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 033 267 A2**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
06.09.2000 Bulletin 2000/36

(51) Int Cl.7: **B60C 11/04, B60C 11/117,  
B60C 11/12**

(21) Application number: **00301515.3**

(22) Date of filing: **25.02.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Ishiyama, Makoto**  
**Tokyo 104-0031 (JP)**

(74) Representative: **Whalley, Kevin**  
**MARKS & CLERK,**  
**57-60 Lincoln's Inn Fields**  
**London WC2A 3LS (GB)**

(30) Priority: **25.02.1999 JP 4847399**


(71) Applicant: **BRIDGESTONE CORPORATION**  
**Tokyo 104-0031 (JP)**

(54) **Pneumatic tire**

(57) A pneumatic tire in which a block formed in a tread surface has, in a ground contacting surface thereof, a closed sipe which is formed so as to not open onto a groove. The sipe has a first opening formed in the ground-contacting surface of the block, a second opening formed at side surfaces of the block, and a hole which communicates the first opening and the second opening. In accordance with this structure, water taken-

in into the sipe from the first opening at the ground-contacting surface of the block is discharged to the second opening contacting at the side surface facing to the groove. As a result, water drainability of the sipe is improved without lowering rigidity of the block. Thus, a ground contacting performance of the block improves. The pneumatic tire therefore has improved performance on wet roads and improved performance on snowy and icy roads without the rigidity of blocks decreasing.

**F I G. 1**



**EP 1 033 267 A2**

Description

BACKGROUND OF THE INVENTION

5 Field of the Invention

[0001] The present invention relates to a pneumatic tire which aims for an improvement in performances on wet roads and in performances on snowy and icy roads.

10 Description of the Related Art

[0002] Pneumatic tires are conventionally provided with sipes in the surfaces of blocks formed on the tread surface. Such tires aim to improve driving performances/braking performances and directional stability on wet road surfaces and snowy and icy road surfaces by increasing the edge effect so as to improve the water drainability.

15 [0003] However, when a large number of sipes which are opened onto the both side surfaces are provided in a block, the problem arises that the rigidity of the block decreases to deteriorate directional stability. Closed sipes, neither of whose ends opens onto grooves, are effective in order to ensure the rigidity of the block. But water cannot drain from the end portions of the sipes into grooves, and thus the problem that drainability is inferior arises.

20 SUMMARY OF THE INVENTION

[0004] The present invention was developed in order to overcome the above-described drawbacks, and an object of the present invention is to provide a pneumatic tire which aims for an improvement in performances on wet roads and performances on snowy and icy roads by improving drainability while maintaining block rigidity.

25 [0005] In order to achieve the above object, the present invention has the following aspects.

[0006] A first aspect of the present invention is a pneumatic tire comprising: a tread surface having a plurality of grooves formed therein which intersect one another, thereby defining a plurality of land portions that each have a ground contacting surface and side surfaces; and at least one water drainage passage provided in the land portion, wherein the water drainage passage is a hole (a communicating hole) formed inside the land portion, the hole has two ends, one end is opened at the ground contacting surface of the land portion, and the other end is opened at the side surface of the land portion.

30 [0007] In accordance with the first aspect, when water is taken-in into the water drainage passage from the portion which is opened at the ground contacting surface, even if the hole of the opening portion at the ground-contacting surface closes up by deformation of the block-shaped land portion due to the block-shaped land portion contacting the road surface, the water within the water drainage passage (the hole) can be discharged, via the hole, to a groove by the opening end at side surfaces.

[0008] Because only the hole, which passes through the interior, is formed as the water drainage passage at the block-shaped land portion, sufficient rigidity of the water drainage passage can be maintained as compared with a block-shaped land portion which is formed with a sipe which is opened at both ends or one end in the contacting surface.

40 [0009] Namely, the drainability of the water drainage passage can be improved without lowering the block rigidity, and the ground contacting ability of the block-shaped land portion can be improved by the improvement in the water drainability. Thus, the performance on wet roads and the performance on snowy and icy roads can be markedly improved.

[0010] In a second aspect of the present invention, the water drainage passage is a hole having a circular or oval cross-section.

45 [0011] In accordance with the second aspect, the cross-section of the hole, which communicates from the ground-contacting surface of the block-shaped land portion to side surface thereof, is circular or oval. Thus, a concentration of stress in the hole can be prevented by those rounded cross-sectional shapes. Accordingly, generation of cracks at the hole due to deformation of the block-shaped land portion can be suppressed.

50 [0012] In a third aspect of the present invention, the cross-section of the hole is a thin, elongated configuration having a longitudinal direction and a transverse direction.

[0013] In accordance with the third aspect, the opening end of the hole at the ground-contacting surface is a thin, elongated configuration having a longitudinal direction and a transverse direction. Therefore, the longitudinal direction of the opening end becomes an edge component, and contributes to directional stability and braking performance.

55 [0014] In a fourth aspect of the present invention, the hole has a curved portion or a bent portion from the ground-contacting surface toward the side surface.

[0015] In accordance with the fourth aspect, by providing a curved portion or a bent portion in the hole, concentration of stress at specific portions can be prevented, and the generation of cracks and the like can be suppressed. The

"curved portion" is a portion which is formed in a continuous curve, and the "bent portion" is a portion bent so as to include an obtuse angle.

# BRIEF DESCRIPTION OF THE DRAWINGS

- [0016] Fig. 1 is a perspective view of a block of a pneumatic tire relating to a first embodiment of the present invention.
- [0017] Fig. 2 is a plan view of a tread of a pneumatic tire relating to the first embodiment of the present invention.
- [0018] Fig. 3 is a perspective view of a block of a pneumatic tire relating to a modified example of the first embodiment.
- [0019] Fig. 4 is a cross-sectional view taken along line 4-4 of Fig. 3.
- [0020] Fig. 5 is a perspective view of a block of a pneumatic tire relating to a second embodiment of the present invention.
- [0021] Fig. 6 is a plan view of a block relating to the second embodiment of the present invention.
- [0022] Fig. 7 is a cross-sectional view taken along line 7-7 of Fig. 6.
- [0023] Fig. 8 is a perspective view of a block of a pneumatic tire used in Comparative Example 1.

# DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0024] A pneumatic tire relating to a first embodiment of the present invention will be described in detail hereinafter. The present first embodiment is described in detail with reference to Figs. 1 through 4.

[0025] As illustrated in Fig. 2, a pneumatic tire 10 comprises a tube-shaped tread 12 which extends across a pair of left and right sidewalls (not illustrated). A plurality of main grooves 14, which are formed along a tire circumferential direction (the direction of arrow P), and a plurality of lug grooves 16, which are formed along the tire transverse direction (the direction of arrow Q), are formed in the tread 12. A plurality of blocks 18 are demarcated by the main grooves 14 and the lug grooves 16. Sipes 22 which extend along the transverse direction of the tire are formed in the blocks 18.

[0026] As illustrated in Fig. 1, the sipe 22 is formed by an opening 22A (first opening) at a ground contacting surface 20 of the block 18, an opening 22B (second opening) which opens at a side surface 18A of the block 18 which side surface 18A faces a lug groove 16, and a hole 22C which is inclined to the openings 22A and 22B.

[0027] Effects of the pneumatic tire 10 structured as described above will be described hereinafter.

[0028] The following effects are obtained by the pneumatic tire 10, which has the blocks 18 in which the sipes 22 are formed, when the pneumatic tire 10 is mounted to a vehicle and the vehicle is run on a wet road surface.

[0029] Due to the block 18 contacting the road surface, water is taken-in into the communicating hole 22C from the opening 22A of the sipe 22 formed in the ground contacting surface 20. Due to the block 18 deforming or the like, the water is confined in the interior of the sipe 22, but it is possible to discharge the water to the lug groove 16 from the (communicating) hole 22C via the opening 22B. Thus, the drainability to drain the water from the road surface to the side surface is improved, and the ground contact performance of the tread 12 (block 18) is also improved.

[0030] Further, the longitudinal direction end portion of the opening 22A of the sipe 22 does not open onto a groove on either side. Therefore, the rigidity of the block 18 can be sufficiently ensured, and the rigidity does not become insufficient due to the provision of the (communicating) hole 22C in the block 18.

[0031] Moreover, because the cross-sectional configuration of the communicating hole 22C of the sipe 22 is a thin, elongated shape, the edge component is sufficiently maintained.

[0032] As a result, the directional stability of the pneumatic tire on wet road surfaces improves.

[0033] The performance of the pneumatic tire 10 of the present invention on wet road surfaces has been described above, and the pneumatic tire 10 also exhibits similar effects on snowy and icy roads.

[0034] In the present embodiment, the (communicating) hole 22C of the sipe 22 is inclined. In other examples, the hole may be formed in a curved configuration (a configuration which bends at an obtuse angle). Namely, as illustrated in Figs. 3 and 4, the hole 22C is formed by a vertical portion 22C1 which is formed vertically from the opening 22A to the ground contacting surface 20, a parallel portion 22C2 which is formed from the opening portion 22B and parallel to the ground contacting surface 20, and a curved portion 22C3 which connects the vertical portion 22C1 and the parallel portion 22C2.

[0035] Next, the pneumatic tire 10 relating to a second embodiment, in which the configuration of the sipe 22 is different than in the first embodiment, will be described with reference to Figs. 5 through 7. Structural elements which are the same as those of the first embodiment are denoted by the same reference numerals, and detailed description thereof is omitted. In the present second embodiment, because only the configuration of the sipe differs from the structure of the first embodiment, only the configuration of the sipe will be explained.

[0036] As illustrated in Figs. 5 and 6, eight holes 30 having a circular cross-sectional configuration are disposed in a square configuration in the ground contacting surface 20 of the block 18. The hole 30 is formed from an opening 30A which is at the ground contacting surface 20, an opening 30B which is formed at one of side surfaces 18A through 18D, and a (communicating) hole 30C which (communicates) the openings 30A, 30B. As illustrated in Fig. 7, the

## EP 1 033 267 A2

(communicating) hole 30C is formed from a vertical portion 30C1 which is formed vertically from the opening 30A to the ground contacting surface 20, a parallel portion 30C2 which is formed parallel to the ground contacting surface 20 from the opening 30B, and a bent portion 30C3 which connects the vertical portion 30C1 and the parallel portion 30C2.

[0037] When the pneumatic tire 10 having the above-described structure is mounted to a vehicle and the vehicle is driven on a wet road surface, the following effects are obtained.

[0038] The water which is taken into the holes 30 from the openings 30A due to the ground contacting surface 20 of the block 18 contacting the ground (or road surface) is discharged via the (communicating) holes 30C and the openings 30B to the main groove 14 or the lug groove 16, so that the drainability of the holes 30 improves. Further, because only eight circular holes 30 are formed in the block 18, the rigidity of the block 18 is sufficiently maintained. As a result, the ground contacting ability of the block 18 improves, and the directional stability on wet road surfaces improves.

[0039] In the present embodiment, because the cross-sectional configuration of the hole 30 is circular, it is possible to restrain concentration of stress on the hole during the deformation of the block 18, and thus the generation of cracks in the hole 30 is suppressed.

[0040] In the present embodiment, the cross-sectional configuration of the hole 30 is circular. The cross-sectional configuration of the hole may be another shape such as oval.

[0041] The properties on wet road surfaces of the pneumatic tire 10 of the present embodiment have been explained above, but the same effects are exhibited on snowy and icy road surfaces.

### Examples

[0042] A directional stability test and a braking performance test were carried out in order to confirm the effects of the pneumatic tire according to the above-described embodiments.

[0043] Comparative Example 1 Tire and Example 1 Tire had, in the blocks of the tread pattern illustrated in Fig. 2, sipes which extended in the tire transverse direction. These blocks were shaped such that the ground contacting surface 20 thereof was a square having a length L of 20 mm, and the height H of the block was 8 mm. Closed sipes which extended in the tire transverse direction and had a length L3 of 10 mm and a width W of 0.6 mm were formed in the blocks. The Comparative Example 1 Tire was formed such that the sipe 22 had a depth D of 6 mm vertically from the ground contacting surface 20, as illustrated in Fig. 8. As illustrated in Fig. 4, the Example 1 Tire was formed such that a distance L1 from side surfaces 18A to the central position of the opening 22A was 10 mm, a depth D1 of the vertical portion 22C1 of the sipe 22 from the ground contacting surface 20 was 4 mm, a distance L2 from the ground contacting surface 20 to the central position of the opening 20B was 7 mm, and a depth D2 of the parallel portion 22C2 of the sipe 22 from side surfaces 18A was 5 mm.

[0044] Tests on the directional stability on dry roads, the directional stability on wet roads, and the directional stability on snowy roads were conducted on test courses (having a dry road surface, a wet road surface, and a snowy road surface, respectively), and the directional stability, lane changing stability, and cornering stability were tested. An experienced driver evaluated these respective performances subjectively, and ranked them with 10 being the highest score possible. The comparison value expressed how much the Example 1 Tire improved with respect to the Comparative Example 1 Tire, and these comparison values are listed in Table 1.

Table 1

	Directional stability on Dry Roads	Directional stability on Wet Roads	Directional stability on Snowy Roads
Comparison Value	±0	2	2

[0045] It was confirmed that, although the directional stability on dry roads of the Example 1 Tire did not differ from that of Comparative Example 1 Tire, the Example 1 Tire did show an improvement with regard to directional stability on wet roads and directional stability on snowy roads.

[0046] An Example 2 tire, in which round holes were formed in the ground contacting surface of each block, and a Comparative Example 2 Tire, in which no such holes were formed, were compared with regard to directional stability on icy roads and braking performance on icy roads.

[0047] Comparative Example 2 Tire and Example 2 Tire had, in the blocks of the tread pattern illustrated in Fig. 2, sipes which extended in the tire transverse direction. These blocks were shaped such that the ground-contacting surface 20 thereof was a square having a length L of 20 mm, and the height H of the block was 8 mm. In the Example 2 Tire, eight holes 30 were formed in a square configuration in the ground-contacting surface 20 (see Figs. 5, 6). As illustrated in Fig. 7, a distance L1 from side surfaces 18A (or 18B or 18C or 18D) to the central position of the opening 30A was 6 mm, a depth D1 of the vertical portion 22C1 of the sipe 22 from the ground contacting surface 20 was 5

## EP 1 033 267 A2

mm, a distance L2 from the ground contacting surface 20 to the central position of the opening 30B was 7 mm, and a depth D2 of the parallel portion 30C2 of the hole 30 from side surfaces 18A was 5 mm.

[0048] In the on-ice directional stability test, at the test course (on an icy road surface), the directional stability, lane changing stability, and cornering stability were tested. An experienced driver evaluated these respective performances subjectively, and ranked them with 10 being the highest score possible. In the on-ice braking performance test, while the vehicle was traveling on an icy road surface at a speed of 40 km/h, it was measured the distance between the point the brake was fully applied and the point the vehicle was completely stopped. The reciprocal of this distance was used to evaluate the braking performance. The comparison value expressed how much the Example 2 Tire improved with respect to the Comparative Example 2 Tire, and these comparison values are listed in Table 2.

Table 2

	Directional stability on Icy Roads	Braking Performance on Icy Roads
Comparison Value	2	40% improvement

[0049] It was confirmed that, by providing holes which extend from the ground-contacting surface of the block to the side surface, the directional stability on icy roads and the braking performance on icy roads markedly improved.

[0050] As described above, the present invention provides a pneumatic tire in which, by forming the water drainage passage (the hole) which communicate from the ground contacting surface to a side surface of a block-shaped land portion, water drainability can be improved without adversely affecting block rigidity, and performance on wet roads and on snowy and icy roads improve.

### Claims

#### 1. A pneumatic tire comprising:

a tread surface having a plurality of grooves formed therein which intersect one another, thereby defining a plurality of land portions that each have a ground contacting surface and side surfaces; and  
at least one water drainage passage provided in each : delete land portion,  
wherein the water drainage passage is a hole formed inside the land portion, and the hole has two ends, one end is opened at the ground-contacting surface of the land portion, and the other end is opened at a side surface of the land portion.

2. A pneumatic tire according to claim 1, wherein the one end of the hole at the ground-contacting surface of the land portion is formed within the ground contacting surface without opening onto a groove.

3. A pneumatic tire according to claim 2, wherein the other end of the hole at side surfaces of the land portion is formed within side surfaces without opening onto a groove.

4. A pneumatic tire according to claim 3, wherein the one end and the other end of the hole are shaped circular, and if not circular, then oval.

5. A pneumatic tire according to claim 4, wherein a cross-sectional configuration of the hole is round, and if not round, then oval.

6. A pneumatic tire according to claim 5, wherein the hole is inclined linearly from the one end towards the other end.

7. A pneumatic tire according to claim 5, wherein the hole has a portion that bends from the one end towards the other end.

8. A pneumatic tire according to claim 7, wherein the hole bends at an obtuse angle at said portion.

9. A pneumatic tire according to claim 3, wherein the one end and the other end of the hole are each formed in a thin, elongated configuration.

10. A pneumatic tire according to claim 9, wherein a cross-section of the hole is formed in a thin, elongated configuration.

EP 1 033 267 A2

11. A pneumatic tire according to claim 10, wherein the hole inclines linearly from the one end towards the other end.

12. A pneumatic tire according to claim 10, wherein the hole has a portion that bends from the one end towards the other end.

13. A pneumatic tire according to claim 12, wherein the hole bends at an obtuse angle at said portion.

14. A pneumatic tire comprising:

a tread surface having a plurality of intersecting grooves, which thereby define a plurality of land portions that each have a ground contacting surface and side surfaces; and

at least one water drainage passage provided in each block-shaped land portion,

wherein the water drainage passage includes:

a first opening end formed within the ground contacting surface of the land portion without opening onto a groove;

a second opening end formed within side surfaces of the land portion without opening onto a groove; and

a hole connecting the first opening and the second opening to one another.

15. A pneumatic tire according to claim 14, wherein the first opening end, the second opening end, and a cross-sectional configuration of the hole is round, and if not round, then oval.

16. A pneumatic tire according to claim 15, wherein the hole has a portion that bends from the first opening towards the second opening.

17. A pneumatic tire according to claim 16, wherein the hole bends at an obtuse angle at said portion.

18. A pneumatic tire according to claim 14, wherein the first opening end, the second opening end, and a cross-section of the hole are each formed in a thin, elongated configuration.

19. A pneumatic tire according to claim 18, wherein the hole has a portion that bends from the first opening towards the second opening.

20. A pneumatic tire according to claim 19, wherein the hole bends at an obtuse angle at said portion.

FIG. 1




FIG. 2






FIG. 3





FIG. 4



F I G. 5




FIG. 6




FIG. 7





FIG. 8



(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 033 267 A3**

(12)

**EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
13.02.2002 Bulletin 2002/07

(51) Int Cl.7: **B60C 11/04**, B60C 11/117,  
B60C 11/12

(43) Date of publication A2:  
06.09.2000 Bulletin 2000/36

(21) Application number: **00301515.3**

(22) Date of filing: **25.02.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(71) Applicant: **BRIDGESTONE CORPORATION**  
**Tokyo 104-0031 (JP)**

(72) Inventor: **Ishiyama, Makoto**  
**Tokyo 104-0031 (JP)**

(30) Priority: **25.02.1999 JP 4847399**


(74) Representative: **Whalley, Kevin**  
**MARKS & CLERK, 57-60 Lincoln's Inn Fields**  
**London WC2A 3LS (GB)**

(54) **Pneumatic tire**

(57) A pneumatic tire in which a block formed in a tread surface has, in a ground contacting surface thereof, a closed sipe which is formed so as to not open onto a groove. The sipe has a first opening formed in the ground-contacting surface of the block, a second opening formed at side surfaces of the block, and a hole which communicates the first opening and the second opening. In accordance with this structure, water taken-

in into the sipe from the first opening at the ground-contacting surface of the block is discharged to the second opening contacting at the side surface facing to the groove. As a result, water drainability of the sipe is improved without lowering rigidity of the block. Thus, a ground contacting performance of the block improves. The pneumatic tire therefore has improved performance on wet roads and improved performance on snowy and icy roads without the rigidity of blocks decreasing.

**F I G. 1**



**EP 1 033 267 A3**



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 00 30 1515

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CI.7)
E	EP 1 034 946 A (MICHELIN RECH TECH ;MICHELIN SOC TECHNOLOGIE (FR)) 13 September 2000 (2000-09-13) * page 2, column 1, line 8 - line 17 * * page 3, column 3, line 1 - line 11; claim 1; figures 1,2,4,6A *	1,9,14, 18	B60C11/04 B60C11/117 B60C11/12
X	EP 0 625 436 A (SEMPERIT AG) 23 November 1994 (1994-11-23) * column 4, line 15 - line 46; claims; figures *	1-8, 14-17	
X	EP 0 654 366 A (BRIDGESTONE CORP) 24 May 1995 (1995-05-24) * page 5, line 19-21; figures 7B,7C *	1	
X	PATENT ABSTRACTS OF JAPAN vol. 015, no. 097 (M-1090), 8 March 1991 (1991-03-08) & JP 02 310108 A (TOYO TIRE & RUBBER CO LTD), 25 December 1990 (1990-12-25) * abstract *	1-5,7,8, 14-17	
A	US 2 575 439 A (BILLINGSLEY WILLIAM F) 20 November 1951 (1951-11-20) * column 2; figures *	1,9	
A	US 3 848 651 A (FRENCH T) 19 November 1974 (1974-11-19) * claims; figures *	1,9,14, 18	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>18 December 2001</b>	Examiner <b>Baradat, J-L</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1533 03/82 (P04C01)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 1515

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-12-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 1034946 A	13-09-2000	FR 2790717 A1	15-09-2000
		EP 1034946 A1	13-09-2000
		JP 2000280715 A	10-10-2000
EP 0625436 A	23-11-1994	AT 403456 B	25-02-1998
		AT 97393 A	15-07-1997
		AT 149432 T	15-03-1997
		DE 59401878 D1	10-04-1997
		EP 0625436 A1	23-11-1994
EP 0654366 A	24-05-1995	DE 69415281 D1	28-01-1999
		DE 69415281 T2	08-07-1999
		EP 0654366 A1	24-05-1995
		FI 944892 A	18-08-1995
		JP 8104112 A	23-04-1996
		NO 944366 A	19-05-1995
		US 5814169 A	29-09-1998
JP 02310108 A	25-12-1990	NONE	
US 2575439 A	20-11-1951	FR 1018836 A	15-01-1953
US 3848651 A	19-11-1974	GB 1407790 A	24-09-1975
		AU 472544 B	27-05-1976
		AU 4671472 A	04-04-1974
		CA 961391 A1	21-01-1975
		DE 2245377 A1	22-03-1973
		ES 406631 A1	01-10-1975
		FR 2152907 A1	27-04-1973
		IE 36923 B1	30-03-1977
		IT 970704 B	20-04-1974
		JP 48037801 A	04-06-1973
		JP 55008361 B	04-03-1980
		MY 19876 A	31-12-1976
		TR 17341 A	24-03-1975
		ZA 7206126 A	27-06-1973

EPO FORM P0489

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**THIS PAGE BLANK (USPTO)**